

Barrington Packaging Systems Group

Integrated Packaging Equipment, Materials, Production Services and Marketing Support

Better Products • Better Prices • Better Service

TUNNELS



BPS 1622 MK Combo

L Bar and Heat Tunnel Shrink System - 2 in 1 System.

L-Sealer

- Power belted discharge conveyor
- Dual magnet clamping
- Pin perforation hold punch
- Variable dwell/seal time
- Variable conveyor time
- Seal head return cylinder
- Locking casters
- Linear bearings allow movement forward or backward

Shrink Tunnel

- Fully re-circulating air chamber
- Live or dead roller rod conveyor
- Digital temperature control
- Adjustable air velocity control
- State-of-the-Art AC variable speed drive
- Automatic tunnel cool down with shut off
- Heats up to 200°C in less than 6 minutes
- Anti-jam safety feature on conveyor

Model	BPS 1622 L Bar	BPS 18028 Shrink Tunnel
Capacity	16"x22" Sealing Size	L 28" x W 18" x H 8" opening
Speeds	10 to 15 per minute	10 to 15 per minute
Electrical	220 VAC / 1ph / 15 FLA	220 VAC / 3ph / 15 FLA
Dimensions	L 61" x W 31" x H 40"	L 40" x W 26" x H 61"

Barrington Packaging Systems Group, Inc.

HQ: 835 Barrington Point, Barrington, IL 60010 • Showroom: 1056 National Pkwy, Schaumburg, IL 60173
Corporate Headquarters (847) 382-8063 • Fax: (847) 382-8064 • Toll-Free: (888) 814-7999
Web: www.barringtonpackagingsystemsgroup.com • Email: info@bpsgusa.com